

Security System Comparison Chart

LEGEND		Yes = Standard Feature	P = Programmable Feature	O = Optional	— = Don't Need / Unrelated	
MODEL NUMBER:		1480B / 1480S	1460B / 1460S	1370B / 1370S	1355B / 1355S	2310B
RETAIL PRICE (excludes tax):		¥46,000 / ¥40,000	¥38,000 / ¥32,000	¥54,000 / OPEN	OPEN / OPEN	¥46,000
Siren, Tx & Control Module Specs.	1 Electronic Siren Model	KB22-1 / KR22-1	KB22-1 / KR22-1	KB22-1 / KR22-1	KB22-1 / KR22-1	KB24-1
	Siren Output Intensity	125dB	125dB	125dB	125dB	125dB
	Siren Tones	"BEEP" 1 Tone	"BEEP" 1 Tone	"BEEP" 1 Tone	"BEEP" 1 Tone	"BEEP" 1 Tone
	Siren Output Duration: Full Blast & Warning	30 sec. & 2 sec.	30 sec. & 2 sec.	30 sec. / 2 sec.	30 sec. & 2 sec.	30 sec. / 2 sec.
	Internal Battery Backup Siren	Yes / —	Yes / —	Yes / —	Yes / —	Yes
	2 Number of Remotes (including pagers)	O	O	1	2 / 2	2 (waterproof)
	3 Rolling Codes (66-bit)	—	—	74x10 ¹⁸	74x10 ¹⁸	74x10 ¹⁸
	4 ARIB STD (Japan) Compliant Remote	—	—	Yes	Yes	—
	5 Remote Battery Life (typical)	—	—	1 to 1.5 months	1 year	1 Year
	6 Remote Battery Type	—	—	1 AAA	1 CR2032	2 CR2032
System Features	7 Transmitter Memory Slots	4, O	4, O	3	3	3
	7 Factory Keyless (SMART-key) Arms/Disarms	Yes	Yes	O	O	O
	8 System Standby Current Consumption	15mA / 9mA	14mA / 8mA	30mA / 25mA	22mA / 16mA	30mA
	Siren Blasting Current Consumption	1A max.	1A max.	1A max.	1A max.	1A max.
	9 Operating Temperature Range	-40 to 85°C	-40 to 85°C	-40 to 85°C	-40 to 85°C	-40 to 85°C
	10 Waterproofing of Control Module & Siren	IP40 & IP54	IP40 & IP54	IP40 & IP54	IP40 & IP54	IP40 & IP54
	11 Japan Car Alarm Standard (VAS) Compliant	Yes	Yes	Yes	Yes	—
	12 Status LED Type (red light)	PBS-90L	PBS-90L	HMLEL-R	HMLEL-R	L-318
	13 Program Switch Included	Yes	Yes	—	—	—
	13 Confirmation Chirps	P (one touch)	P (one touch)	P (one touch)	P (one touch)	P (one touch)
Sensor Protection	14 2-way Answer-Back (Pager) Functionality	O	O	Yes	—	—
	15 Siren Trigger Memory	Yes	Yes	Yes	Yes	Yes
	16 Triggered Sector Memory	Yes	Yes	via Pager Icons	—	—
	17 High Security Disarm	O	O	Yes	Yes	Yes
	18 Auto Arm	P	P	P	P	P
	19 Auto Rearm	P	P	P	P	P
	20 Panic Siren Mode	O	O	P	P	P
	21 Error Chirp	Yes	Yes	Yes	Yes	Yes
	22 SBS (Sector Bypass System)	Yes	Yes	Yes	Yes	Yes
	23 Bypass Triggers: Sensor/WARN/SensorFull/Door/IG	10/10/5/10	10/10/5/10	10/10/5/10	10/10/5/10	10/10/5/10
Outputs	23 Manual Disarm	Yes	Yes	Yes	Yes	Yes
	24 Programmable Disarm Code	P	P	P	P	P
	25 Remote Start Compatible	P (Note 1)	P (Note 1)	P	P	P
	26 Turbo Timer Compatible	P (Note 1)	—	P	P	P
	27 Speed-Controlled Door Lock	P (Note 3)	—	—	—	—
	28 Silent Mode	O	O	P	P	P
	29 Shock Sensor Bypass Mode	P	P	P	P	P
	30 Direct Door Lock	O	—	P	P	P
	31 Valet Mode	P	P	—	—	—
	32 Car Locator Mode	O	O	Yes	—	—
Outputs	33 DIGI [∞] LINK (CAN-BUS) Interface	Yes	—	O	O	—
	34 2-Stage Active-IR Shock Sensor	Yes	Yes	Yes	Yes	Yes
	35 Door Open Trigger Input (-)	Yes	Yes	Yes	Yes	Yes
	36 Ignition Switch Trigger Input	Yes	Yes	Yes	Yes	Yes
	37 IIP (Intelligent Ignition Protection)	P	P	P	P	P
	38 Dual Protection	Yes	Yes	Yes	Yes	Yes
	39 Trunk Open Trigger Input	Yes	Note 2	Note 2	Note 2	Yes
	40 Hood Open Trigger Input	Note 2	Note 2	Note 2	Note 2	Note 2
	41 Starter Kill Immobilizer	O	O	O	O	3-Point Cut
	42 "Resume" Memory	Yes	Yes	Yes	Yes	Yes
43 GWA Control Output (-)	Yes	Yes	Yes	Yes	Yes	
44 Hazard Light Flash Output (-)	Yes (Note 3)	Parking Lights (-)	Yes	Yes	Yes	
45 Door Lock Control Output	O (Note 3)	O	Yes (-)	Yes (-)	Yes (-)	
46 Hazards Flash if Door Opens while IG ON	P (Note 3)	—	—	—	—	
47 Exterior Illumination	P (Note 3)	P	P	P	P	
48 Channel Output (Trunk Release)	O (Note 3)	O	—	—	—	
49 Remote Start Confirmation	P (Note 3)	P	P	P	P	

* You must have specialized knowledge about vehicle electronics and experience with electronic alarm system wiring to install VISION security products.
 * Push-Start Ignition vehicles will require our optional PBS-90 Program Switch when installing all Vision Security Systems, except the 1480 & 1460 series.
 * Some vehicles may require optional parts for door lock control.
 * Features and specifications subject to change without notice. Consult Owner's & Installation Guides for latest specifications and details on product warranty.
 * Please consult with a professional installer to determine installation cost and to determine if installation is actually possible in your vehicle.
 * Some non-Japanese cars may not be able to use the door locking and/or light flashing features.
 * On vehicles with factory alarms, door lock/unlock may or may not be possible via the remote of the 1355 or 1370 series products.
 * Backup siren internal batteries are not user-replaceable and typically last 2-3 years. We do not sell replacement batteries. Also note that backup sirens draw 5mA constantly, Armed or Disarmed, to trickle-charge the siren's battery.
 * Putting a VISION pager remote on the same keychain as your factory keyless fob may result in RF interference that will not allow either the fob or the pager to function properly. Separate each remote by 10cm.
 * Prices listed do not include installation. "OPEN" price is explained on our website here: <https://www.kiramek.com/english/sales.html#CompetitivePricing>

Note 1: Although the 1460 is fully compatible with remote engine starters and turbo timers, it is important to keep in mind that many vehicles won't allow keyless door locking/unlocking while the remote starter or turbo timer is in use. This means you will not be able to arm or disarm the 1460 while the remote starter or turbo timer is running in such vehicles. But for vehicles that allow keyless locking/unlocking while the engine is running, you will be able to arm or disarm the 1460 while the remote starter or turbo timer is operating.
Note 2: There are no separate inputs for Trunk or Hood on these systems. The input splices off the door trigger input. Optional Hood switch required for sensing hood opening on many cars.
Note 3: Feature may not function properly or at all on some cars.